



The Gorman-Rupp Company

GHA Series (G Series)

The GHA Series is designed for continuous duty service for applications in the operating ranges noted. These units are available with head and backhead jackets for temperature control, along with packing or mechanical seal options. This abrasive handling, extreme duty series, provides superior wear resistance. The design also provides superior rotor shaft support and an integral, maintenance-free radial/thrust bearing for reduced deflection and wear. Reduced speeds enable service over extended periods.



Specifications

Size:	1" (25 mm), 2" (50 mm), 3" (75 mm), 4" (100 mm), 6" (150 mm)
Max Capacity:	325 GPM (21 lps)
Max Viscosity:	250,000 SSU (54,000 cST)
Max Pressure:	200 PSI (14 BAR)
Min Temperature:	-60 F (-51 C)
Max Temperature:	500 F (260 C)
Materials of Construction:	Cast Iron, Hard Iron

Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.



The Gorman-Rupp Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1251
E-mail:
grsales@gormanrupp.com

The Gorman-Rupp International Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1266
E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
70 Burwell Road
St. Thomas, Ontario N5P 3R7,
Canada
Tel: 519-631-2870
Fax: 519-631-4624
E-mail: grcanada@grcanada.com



www.grpumps.com

©2005-2006 The Gorman-Rupp Company. All Rights Reserved.